

**Appl. No. 09/513,962  
Amendment and/or Response  
Reply to Office action of 14 September 2004**

**Page 2 of 8**

**Amendments to the Claims:**

A listing of the entire set of pending claims (including amendments to the claims, if any) is submitted herewith per 37 CFR 1.121. This listing of claims will replace all prior versions, and listings, of claims in the application.

**Listing of Claims:**

1. (Canceled.)

2. (Previously presented) A communications system for receiving a plurality of messages from a plurality of transmitters, comprising:

a receiver that is configured to receive a composite signal that comprises the plurality of messages from the plurality of transmitters, each message having a transmitter code-phase relative to a code-phase of the receiver, each transmitter code-phase being independent of the code-phase of the receiver, and

a message discriminator that is configured to discriminate at least one message from the plurality of messages based on the transmitter code-phase corresponding to the at least one message,

wherein the message discriminator comprises:

a delay element, operably coupled to the receiver, that is configured to provide a message sample from the composite signal, the message sample corresponding to a select transmitter code-phase relative to the code-phase of the receiver,

a decoder, operably coupled to the delay element, that is configured to decode the message sample based on a receiver code at the code-phase of the receiver, and thereby provide a decoded message sample at the select transmitter code-phase, and

a threshold detector, operably coupled to the decoder, that is configured to discriminate the at least one message corresponding to the decoded message sample, based on a composite energy component of the decoded message sample at the select transmitter code-phase.

**Appl. No. 09/513,962**  
**Amendment and/or Response**  
**Reply to Office action of 14 September 2004**

**Page 3 of 8**

3. (Previously presented) The communications system of claim 2, further comprising  
at least one queue device that is configured to receive the decoded message sample  
from the decoder for the at least one message at the select transmitter code-phase.
4. (Original) The communications system of claim 2, wherein the receiver code comprises a  
pseudo-random noise direct-sequence spread-spectrum (DSSS) code.
5. (Previously presented) The communications system of claim 2, wherein  
the receiver includes  
a downconverter that is configured to provide a downconverted composite  
signal above a baseband frequency of the plurality of messages, and  
the decoder includes  
a Fast Fourier Transform (FFT) element that is configured to determine the  
composite energy component.
6. (Previously presented) The communications system of claim 5, wherein  
the Fast Fourier Transform (FFT) element comprises a number of nodes that propagate  
values to provide the determination of the composite energy component, and  
the number of nodes is dependent upon a bandwidth corresponding to a variance of  
transmit frequencies associated with the plurality of transmitters.
7. (Previously presented) The communications system of claim 5, wherein  
the Fast Fourier Transform (FFT) element is also configured to determine a bit-phase  
corresponding to the decoded message sample, and  
a content of the at least one message is based upon the bit-phase corresponding to the  
decoded message sample.
8. (Original) The communications system of claim 7, wherein  
the content of the at least one message is further based on a predicted bit-phase that is  
based on a plurality of bit-phases of prior message samples.

Appl. No. 09/513,962  
Amendment and/or Response  
Reply to Office action of 14 September 2004

Page 4 of 8

9. (Previously presented) The communications system of claim 2, further comprising  
a satellite that is configured to receive the plurality of messages from the plurality of transmitters, and to provide therefrom the composite signal to the receiver.

10. (Previously presented) The communications system of claim 2, further comprising:  
at least one other decoder, operably coupled to the delay element, that is configured to decode the message sample based on an at least one other receiver code at the code-phase of the receiver, and thereby provide at least one other decoded message sample at the select transmitter code-phase.

11. (Currently amended) A communications system comprising:  
a plurality of transmitters that are configured to communicate messages to a receiver,  
each transmitter of the plurality of transmitters being configured to operate substantially autonomously, and independent of the receiver, and each transmitter being configured to communicate its message to the receiver using substantially identical transmission parameters as each other transmitter, including using a common spreading-code within a common communications channel, and

wherein

each message has an associated code-phase that is independent of the receiver, and independent of each other message, and does not include a substantial sequence of bits that are common among each of the other messages thereby facilitating a discrimination of the messages at the receiver based on different code-phases associated with different messages.

12. (Original) The communications system of claim 11, wherein  
each message contains an error correction code that facilitates a determination of a content of each message when individual content elements of each message are not received.

13. (Canceled)

**Appl. No. 09/513,962**  
**Amendment and/or Response**  
**Reply to Office action of 14 September 2004**

**Page 5 of 8**

14. (Previously presented) A method of communication comprising:

receiving a composite signal that comprises a plurality of messages from a plurality of transmitters, each message having a transmitter code-phase relative to a code-phase of the receiver, each transmitter code-phase being independent of the code-phase of the receiver, and

discriminating at least one message from the plurality of messages based on the transmitter code-phase corresponding to the at least one message,

wherein discriminating the at least one message includes:

sampling the composite signal to provide a message sample, the message sample corresponding to a select transmitter code-phase relative to the code-phase of the receiver,

decoding the message sample based on a receiver code at the code-phase of the receiver to provide a decoded message sample at the select transmitter code-phase, and

determining an energy component of the decoded message sample at the select transmitter code-phase,

comparing the energy component to a threshold value to discriminate the at least one message corresponding to the decoded message sample.

15. (Original) The method of claim 14, further comprising:

determining a decoded message value from the decoded message sample, and

queuing the decoded message sample in a queue that is associated with the select transmitter code-phase to form the at least one message.

16. (Original) The method of claim 14, wherein the receiver code comprises a pseudo-random noise direct sequence spread-spectrum (DSSS) code.

**Appl. No. 09/513,962**  
**Amendment and/or Response**  
**Reply to Office action of 14 September 2004**

**Page 6 of 8**

17. (Original) The method of claim 14, wherein receiving the composite signal includes  
downconverting the composite signal to provide a downconverted composite signal  
above a baseband frequency of the plurality of messages, and  
transforming the downconverted composite signal via a Fourier transform to  
determine the composite energy component.

18. (Original) The method of claim 17, wherein  
transforming the downconverted composite signal via the Fourier transform also  
provides a bit-phase corresponding to the decoded message sample, and  
determining a decoded message value based upon the bit-phase corresponding to the  
decoded message sample.

19. (Original) The method of claim 18, wherein  
the content of the at least one message is further based on a predicted bit-phase that is  
based on a plurality of bit-phases of prior message samples.

20. (Original) The method of claim 19, further comprising  
receiving the plurality of messages from the plurality of transmitters via a satellite and  
providing thereby the composite signal to the receiver.